



NON-INSULATED RING LUG

Key Features:

– A ring terminal is a short metal tube with flat washer type ring attached. The barrel end of the crimp is a hollow tube where the stranded wire is inserted and crimped. The contact or connection end is a flat ring with a central hole which connects to a bolt



Materials/Finish:

– Terminals are made from electrolytic copper, tin-plated finish to improve electrical contact

Type	WIRE RANGE		DIMENSIONS						
	AWG/MCM	mm ²	ΦE	ΦD	Φd	W	B	L	T
1.25-3	22-16	0.25-1.65	3.7	3.4	1.7	5.5	4.5	11.5	0.8
1.25-4M			4.3	3.4	1.7	6.6	4.5	14.4	0.8
1.25-5			5.3	3.4	1.7	8	4.5	15.8	0.8
1.25-6			6.4	3.4	1.7	11.6	4.5	21.7	0.8
1.25-8			8.4	3.4	1.7	11.6	4.5	21.7	0.8
1.25-10			10.5	3.4	1.7	13.6	4.5	26	0.8
2-3M			3.7	4	2.3	6.6	4.8	14.4	0.8
2-4M			4.3	4	2.3	6.6	4.8	14.4	0.8
2-5			5.3	4	2.3	9.5	4.8	16.8	0.8
2-6			6.4	4	2.3	12	4.8	21.8	0.8
2-8			8.4	4	2.3	12	4.8	21.8	0.8
2-10			10.5	4	2.3	13.6	4.8	25.5	0.8
5.5-3	8	4.60-6.64	3.7	5.6	3.5	9.5	6.8	19.8	1
5.5-4			4.3	5.6	3.5	9.5	6.8	19.8	1
5.5-5			5.3	5.6	3.5	9.5	6.8	19.8	1
5.5-6			6.4	5.6	3.5	12	6.8	25.8	1
5.5-6S			6.4	5.6	3.5	12	6.8	22.5	1
5.5-8			8.4	5.6	3.5	15	6.8	28	1
5.5-10			10.5	5.6	3.5	15	6.8	28	1
5.5-12			13	5.6	3.5	18.2	6.8	28	1

