



NON-INSULATED FORK TERMINALS (Y LUG)

Key Features:

- Brazed seam protects terminal barrel from splitting during the crimp process
- Fork design provides for fast and easy installation, without the need to remove fastener

Materials/Finish:

- Terminals are made from electrolytic copper, tin-plated finish to improve electrical contact



Type	Wire Range	DIMENSIONS								
		AWG/MCM	mm ²	ΦE	C	A	D	B	L	T
1.25-3YS	1.5	22-16	0.25-1.65	3.7	3.4	1.7	5.7	4.5	16	0.8
1.25-3YW				3.7	3.4	1.7	6.2	4.5	16	
1.25-3YSA				3.2	3.4	1.7	5.7	4.5	16	
1.25-4YS				4.3	3.4	1.7	6.4	4.5	16	
1.25-4YW				4.3	3.4	1.7	7.2	4.5	16	
1.25-5Y				5.3	3.4	1.7	8	5	16	
1.25-6Y				6.7	3.4	1.7	10.7	4.5	17	
2-3YSA	2.5	16-14	1.04-2.63	3.2	4	2.3	5.7	4.5	16	0.8
2-3YS				3.7	4	2.3	5.7	4.5	16	
2-3YW				3.7	4	2.3	6.2	4.5	16	
2-4YS				4.3	4	2.3	6.4	4.5	16	
2-4YW				4.3	4	2.3	7.2	4.5	16	
2-5Y				5.3	4	2.3	8	4.5	16	
2-6Y				6.7	4	2.3	10.7	4.5	19	
3.5-4Y	14-12	2.63-4.60		4.3	5	3.2	8	6.3	18	0.8
3.5-5Y				5.3	5	3.2	8	6.3	18	
5.5-3Y	12-10	4.60-6.64		3.7	5.6	3.5	8.2	6.5	19.5	1
5.5-4Y				4.3	5.6	3.5	8.2	6.5	19.5	
5.5-5Y				5.3	5.6	3.5	9	6.5	19.5	
5.5-6Y				6.4	5.6	3.5	12	6.5	24	
8-5Y	8	6.64-10.52		5.3	7	4.5	9	8.6	23.5	1.15
8-6Y				6.7	7	4.5	12	8.6	24	
14-5Y	6	10.52-16.78		5.3	8.5	5.9	12	10	27.5	1.2
14-6Y				6.7	8.5	5.9	12	10	27.5	
LI14-5I				5.3	9.1	6	12	10	27.5	

