

MINI-TYPE SELF-ADJUSTABLE CRIMPING TOOL

HSC8 6-4



HSC8 16-4



- Applicable for tubular bare terminals and pre-insulated terminals where welding is not needed.
- Terminals to be inserted laterally when crimping.
- Intricately designed crimping dies set and self-releasing integral locking mechanism ensures high quality crimping results, even after long usage.
- When the desired crimping pressure is reached, the lock automatically release the jaws of the pliers; thus resulting in the desired crimping effect.

HSC8 6-4

Specifications	
Capacity	0.25-6mm ²
AWG	24-10
Length (mm)	175
Weight (kg)	0.36

HSC8 16-4

Specifications	
Capacity	4-16mm ²
AWG	12-6
Length (mm)	210
Weight (kg)	0.52

Mini Self Adjustable Crimping Tool (Hexagonal)

HSC86-6A



- Ferrule insertion on the side of the tool
- Self-adjusting adaptation to the desired end sleeve (ferrule) size,
- no wrong crimps caused by using the wrong die
- Fits all ferrules within the application range
- Chrome vanadium electric steel in special quality, oil-hardened

Specifications	HT315
Capacity (mm ²)	0.25-6
AWG	24-10
Length (mm)	175
Weight (kg)	0.4/0.44